APPENDIX B

Cheboygan River/Lower Black River Watershed Streambank Erosion Severity Index

Condition of bank	Points	Soil type or texture	Points
Toe and upper bank eroding	5	Sand	3
Toe undercutting	3	Gravel	2
Toe stable, upper bank eroding	1	Stratified	2
		Clay, loam	1
Problem trend		Vegetative cover on bank slope	
Increasing	5	0-10%	5
Decreasing or stable	1	10-50%	3
-		40-100%	1
Side-slope of bank		Apparent cause of erosion	
Vertical, 1:1	5	Light access traffic	1
2:1, 3:1	2	Obstruction in river	1
4:1 or flatter	1	Bank seepage	1
		Gullying by side channels	1
		Bend in river	2
		Wave action (impoundments)	2 2 3
		Road-stream crossing;	3
		grade/shoulder runoff	
		Moderate access traffic	3
		Heavy access (foot, horse, etc.)	5
		traffic	
Length of eroded bank	_	Mean height of eroded bank	_
More than 50 ft.	5	More than 20 ft	7
20 to 50 ft.	3	10 to 20 ft	5
Less than 20 ft.	1	5 to 10 ft	3
		less than 5 ft	1
Depth of river		Current	
3 ft or over	2	Fast	2
Less than 3 ft	1	Slow	1
Total Points for Site			

Accumulative points indicate extent of erosion, i. e., the site rating, as follows:

More than 36----Severe 30 to 36-----Moderate Less than 30-----Minor